



## Epson SureColor SC-S60600

- Produce durable outdoor signs and banners, window and back-lit displays, wallpaper and decor, vehicle wraps and POS, labels and more... AT HIGH SPEED
- Compatible with coated and uncoated paper, vinyl, canvas, film and synthetic stocks
- Superior imaging with reduced grain, an enhanced gamut, maximum contrast and gloss levels
- Supports tiling applications with exceptional colour precision, consistency and linearity
- Low running costs with reduced power consumption, ink consumption and maintenance
- Easy to operate with a see-through platen cover, remote management & status notification
- Extremely fast job completion with an integrated auto take-up and high speed driver
- Enhanced reliability with a self cleaning printhead, headguard, and air filtration system
- Suits installation in factory, shop and air-conditioned studio environments
- Cost effective operation with low maintenance, power and ink consumption
- High durability with flexible cover extendable up to FIVE YEARS

## **Epson SureColor SC-S60600**

Product Specifications	
PRINTING TECHNOLOGY	
Print Engine  Media Handling	Self-cleaning DUAL PrecisionCore™ TFP with VSDT Epson Precision Dot Technology Integrated headguard Auto media setting, auto skew correction, advanced auto tension control (Ad-ATC) & auto take-up (ATU), Print drying system INCLUDED
Print Quality	1440 x 1440 dpi max res, 4.2 pl min drop size
INK SYSTEM	
Type Colour Set Loading	Epson UltraChrome® GS3 Eco-Solvent DUAL CMYK 8 x 700 ml cartridge
PRINT SPEEDS <sup>1</sup>	
Draft Billboard Banner Vinyl, Canvas & Paper Film (Front & Backlit)	95.3 m²/h 52.3 m²/h 29.4 m²/h 17.6 m²/h 6.8 m²/h
MEDIA HANDLING	
Sizing Input Output Drying	300-1626 mm (64") wide, 1 mm max thickness Single roll, 45 kg max weight, 250 mm max diamete Sheet (manual cut) or roll (200 mm max diameter) Individually adjustable input, platen & output heaters
MANAGEMENT	
Features	See-through platen with LED lighting On-board 2.7" Colour LCD panel Supplied with Epson Control Dashboard software Remote e-mail status & error reporting Supports most major 3rd party RIP applications

INTEGRATION	
Space Requirements	3.6 x 2.7 x 1.7 m (WxDxH)
Operational Temp	15 to 35°C (20 to 32°C recommended)
Operational Humidity	20 to 80% (40 to 60% recommended)
Power Requirement	3 x 240 V, 50/60 Hz, 5 A
Power Consumption	745 W operating/ 13 W sleep
Operational Noise	60.5 dB
Connectivity	USB2.0, 100BASE-TX/1000BASE-T
OPTIONS	
1YWSCS60600	1 Yr CoverPlus On-Site Service Extension
2YWSCS60600	2 Yr CoverPlus On-Site Service Extension
CONSUMABLES	
C13T724100	Maintenance cleaning kit
C135210044	Maintenance parts kit
C13T699300	Ink cleaner
C13T833192	700 ml black ink cartridge
C13T833292	700 ml cyan ink cartridge
C13T833392	700 ml magenta ink cartridge
C13T833492	700 ml yellow ink cartridge
C13T833092	Cleaning cartridge
C13T835192~492	700 ml KCMY 3M™ MCS™ ink cartridges <sup>2</sup>
CONFIGURATION OPTIONS	
SCS606001YR	Printer with 1 Yr On-site Warranty
SCS606003YR	Printer with 1 Yr Wty & 2 Yr On-site CoverPlus
SCS606005YR	Printer with 1 Yr Wty & 2 x 2 Yr On-site CoverPlus
1 Figures are maximum engine encode only. They do not include provisions for image processing	

<sup>&</sup>lt;sup>1</sup> Figures are maximum engine speeds only. They do not include provisions for image processing, transfer, drying or post production. Nominated speeds may not be suitable for all media types and/or applications. Alternate print modes may be employed by RIP s/w for different results.
<sup>2</sup> For details on the MCS program including coverage, certification, terms & conditions please contact your local 3M office.



The **included** print drying system integrates with the printer to enable production at high speed and with heavy ink loads



The Ad-ATC and ATU enable roll-to-roll production with superior linearity, parallelism, and tension for off-line processing and tiling applications





The auto head cleaning & air filtration systems work in conjunction with the headguard to ensure superior reliability with reduced maintenance





The printer can be managed through the control panel or via Epson Control Dashboard s/w complete with e-mail status & error notifications

## Better Products for a Better Future

Epson, SureColor, UltraChrome, PrecisionCore are registered trademarks of Seiko Epson Corporation. All other names and logos herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. All print samples shown herein are simulations. Specifications are subject to change without notice; customers should review material posted on the web sites listed below for the latest information.

3M" MCS" Warranty





March 2018