



Epson Auto Table for SD-10

- Specifically designed table kit for the Epson SD-10 spectrophotometer* to automate colour measuring and create media profiles without any technical knowledge
- Comes with colour management software, Epson Edge Color Lite** (for Epson Edge Print PRO)
- · Verify and unify output colour across multiple Epson printers of the same model
- Supports colour chart media sizes up to 331 mm high, 13 mm thick and virtually any length, including textile media
- Automatic media position and thickness detection by optical sensors measure a 379 colour patch chart in less than five minutes
- Calibrate and maintain stable output colour over an extended period on the same printer
- Create optimised colour media profiles, including fluorescent for SC-F6460H and SC-F10060H

^{*}Sold separately or as a bundle

^{**}Requires PORT activation

Epson Auto Table for SD-10

| Product Specifications | | | |
|------------------------|--|---|--|
| Media Support | | Environmental | |
| Max media thickness | 13 mm | Operating temperature | 10 to 35°C |
| Patch size | $14 \times 14 \text{ mm}$ | Storage temperature | Before unpacking: -20 to 60°C1 |
| Media size | 331 mm high x virtually any length | | After unpacking: -20 to 40°C ² |
| Physical | | Operating humidity | 20 to 80% with no condensation |
| Device (W x H x D) | $550 \times 128 \times 395$ mm, 3.4 kg | Storage humidity | 5 to 85% with no condensation |
| Carry case (W x H x D) | 570 x 145 x 414 mm | Pollution degree | PD2 |
| Operation | | IP Protection Class | IPX0 |
| Interface | High-speed USB Type-B connector | Altitude | 2,000 m or less |
| Support OS | Windows 11 (64-bit), Windows 10 (64-bit), Windows 8.1 (64-bit) | What's in the box | |
| Software | Epson Edge Color Lite, Epson Edge Print/Epson Edge Print PRO (version 5.5.0) | Auto Table, paper sheet manual, carry case, AC cable, USB cable, CD-ROM with licence document, masking tape | |
| Support ICC format | Version 2, 4 | Configurations Options | |
| Support measured file | CGTAS txt file (Lab or Spectrum data) | B42B900311 | Auto Table for SD-10 with 1-yr warranty |
| Power Supply | 100 – 240 V 0.6 A – 0.4 A 50/60 Hz AC | AUTOTABLE3YR | Auto Table for SD-10 with 1-yr warranty + 2-yr CoverPlus (3 yrs total cover) |
| Input voltage range | AC100 – 240 V | AUTOTABLE5YR | Auto Table for SD-10 with 1-yr warranty + 4-yr CoverPlus (5 yrs total cover) |
| Rated current | 0.6 A - 0.4 A | | |
| Rated frequency | 50/60 Hz | SD10TABLE1YR | SD-10 + Auto Table with 1-yr warranty |
| | | SD10TABLE3YR | SD-10 + Auto Table with 1-yr warranty + 2-yr CoverPlus (3 yrs total cover) |
| | | SD10TABLE5YR | SD-10 + Auto Table with 1-yr warranty + 4-yr CoverPlus (5 yrs total cover) |

¹ Can be stored for one month at 40°C, or for 120 hours at 60°C

² Can be stored for one month at 40°C



Unified colour output among multiple Epson printers of the same model





Auto Table in the carrycase



Automatic media thickness and position detection



Epson Edge Color Lite





Epson Australia Pty Ltd Level 1, 3 Talavera Road Macquarie Park NSW 2113 Tel: 02 8899 3666 www.epson.com.au Epson New Zealand Level 2, 9 Fanshawe Street Auckland 1010 Tel: 09 366 6855 www.epson.co.nz 05/2024

