


## Epson Stylus® TX550W

Print | Scan | Copy | Photo | WiFi

Smart. Simple. Amazing







\*Memory card not included

## Features and Benefits

- Fast print speeds up to 36ppm
- 4 Individual Ink Cartridges only replace the colour you use
- High & Extra High capacities available for enhanced productivity and savings
- Epson DURABrite® Ultra Resin
  Coated Pigment Ink for water, smudge
  & fade resistant prints
- Easily share, edit and print photos with a 2.5" LCD screen + memory card slots + PictBridge
- Cable-free printing with 802.11b/g
  Wi-Fi connectivity + 10/100 Ethernet

| Printer   |  |
|---|--|
| PRINTER TYPE                                      |  |
|   | 0110440401   |
| Epson Stylus® TX550W                              | C11CA48401   |
| PRINTING METHOD                                   | On-demand Inkjet (piezoelectric)   |
| NOZZLE CONFIGURATION                              | 384 nozzles Black, 128 nozzles each colour (Cyan, Yellow, Magenta)   |
| MINIMUM INK DROPLET VOLUME                        | 2 Picolitres   |
| RESOLUTION  |  |
| 5760 x 1440 optimised dpi with (with Va           | riable Sized Droplet Technology)   |
| PRINT SPEED                                       |  |
| BLACK TEXT (MEMO) A4 (Draft)^                     | 36ppm*   |
| COLOUR TEXT (MEMO) A4 (Draft)^                    | 36ppm*   |
| Photo 4" x 6" (10 x 15cm) (Draft)^                | Approx. 20 sec*+   |
| Print Speed Data Printout Patterns The thumbna    | il images below show the printout patterns used to determine print speed   |
| specifications.                                   |  |
|   | The committee of the co |
|   | one page. The computer environment we test under is as follows: CPU: XP professional; Interface/Connectivity: USB2.0 HighSpeed; SOFTWARE:  |
| Word XP/PhotoShop7.0; PAPER: Epson Premium        |  |
| Word ALT HotoShopT.0, LAI En. Epson Freihidh      | i diossy i noto i aper oi i laiiri aper  |
| + When printed on Epson Premium Glossy Photo      | Paper  |
| PAPER HANDLING                                    |  |
| PAPER SIZES                                       | A4, Letter, Legal, 8x10", 5x7", 4x6", 3.5x5", 5x8", A6, A5, B5, Half   |
|   | Letter, Envelopes: No10, DL, C6  |
| PAPER HOLD CAPACITY                               | Input capacity: 120 sheets, A4 Plain paper (60g/m2)  |
| True BorderFree™ printing is available for the fo | ollowing media sizes: 4"x6", 5"x7" and A4.   |
| Media tynes recommended: Premium Glossy Ph        | oto paper A4, 4"x6" and 5"x7", Matte Paper - Heavyweight.  |
|   | paper 741, 4 x0 and 6 x7 ; matter aper meavyweight.  |
| BorderFree prints are media dependent.            |  |
| Scanner   |  |
| SCANNER TYPE                                      | A 4 Flathad colour image accessor  |
| *********   | A4 Flatbed colour image scanner  |
| SENSOR TYPE                                       | CIS  |
| DOCUMENT SIZE                                     | Up to A4   |
| PIXEL DEPTH                                       | Input 48bits (16bits/colour) / output 24bits (8bits/colour)  |
| SCANNING RESOLUTION                               | 2400 x 2400 dpi  |
| MONO SCAN SPEED                                   | A4 300dpi 1.1mSec/line   |
|   | A4 600dpi 2.0msec/line   |
|   | A4 1200dpi 3.8msec/line  |
| COLOUR SCAN SPEED                                 | A4 300dpi 3.2msec/line   |
|   | A4 600dpi 5.8msec/line   |
|   | A4 1200dpi 11.2msec/line   |
| Came Function                                     |  |
| Copy Function                                     |  |
| COPY SPEED  |  |
| Copy Speed Black Text Memo (A4)+                  | Approx. 36cpm (Draft)  |
| Copy Speed Colour Text Memo (A4)+                 | Approx. 36cpm (Draft)  |
| General   |  |
| OPERATING SYSTEMS                                 |  |
|   | Windows @ 7/7 044/1-t- 4/1-t- 044//DA/D 04/0000 May @ 00   |
| PRINTER DRIVERS*                                  | Windows® 7/7x64/Vista/Vista64/XP/XPx64/2000, Mac® OS 10.3.9 or later with USB*   |
| * Drivere if eveilable are developed by           |  |
| * Drivers if available are downloadable from      | lech Epson   |
| ELECTRICAL SPECIFICATIONS                         |  |
| RATED VOLTAGE                                     | AC 220 ~ 240V  |
| RATED FREQUENCY                                   | 50 ~ 60Hz  |
| POWER CONSUMPTION                                 | Approx. 16W (ISO/IEC 24712), 4.0W (Sleep Mode)   |
| NOISE LEVEL                                       |  |
| NOISE LEVEL                                       | 5.5B, 42.5dB(ISO9296)  |
| INTERFACES  |  |
| CONNECTIVITY                                      | USB — Compatible with the USB 2.0 Specification (cable included)   |
| MOBILE DEVICE PRINTING                            | Yes - Epson iPrint (wireless photo printing from Apple® iPod   |
|   | Touch®, iPhone® & iPad™ - downloadable from Apple iTunes®  |
|   | Store)   |
| NETWORKING  | 802.11b/g WiFi   |
| NETWORKING  | 10-Base-T, 100 Base-TX Ethernet (cable included)   |

| CARD SLOTS   | CF Type II, Memory Stick, SD/MMC, XD-Picture card  |  |
|--|--|--|
| PICTBRIDGE   | Yes  |  |
| PRINTER SOFTWARE (AVAILABLE ON CD-ROM ONLY)  |  |  |
| SOFTWARE TOOLS   | Epson File Manager<br>Epson Scan Assist<br>Epson Attach to Email<br>Epson Easy Photo Print           |  |
| WARRANTY   |  |  |
|  | 12 months return to base Standard<br>Optional Additional 2 Year Warranty 3YWTX550W<br>Epson Warranty |  |
| PRODUCT DIMENSIONS   | 450mm (W) x 342mm (D) x 182mm (H)  |  |
| WEIGHT   | 6.1kg  |  |
| LIGHTFASTNESS  |  |  |
| LIGHTFASTNESS#   | 120 years on Epson Matte Paper Heavyweight   |  |
| LIGHTFASTNESS TEST CRITERIA (INDOOR DISPLAY CONDITIONS)  |  |  |
| Light source   | Fluorescent light  |  |
| Intensity  | 70k lux  |  |
| Temperature  | 24°C   |  |
| Humidity   | 60% RH   |  |
| Glass Mount  | 2mm, soda lime   |  |
| Fade Criteria  | Pure YMC 30% loss at 0D=1  |  |
| Display Life Calculation   | Total illuminance/(500 lux x 10 hours x 365 days = 1 year)   |  |
| Tests developed and conducted by Epson under fluorescent light (indoor display condition) with glass mount. The data is calculated by Epson's accelerated test of prints on specialty media. |  |  |

# Data is calculated using accelerated simulation of fading under indoor preservation conditions including fluorescent light indoor display. Temperature, humidity and some atmospheric gases may also affect the rate of fading. The estimated lightfastness period does not indicate the colour changing or the durability of the paper itself. Epson recommends that your prints be stored in a photo album (or plastic photo storage box) in acid free, archival sleeves commonly available from most

| INK CARTRIDGES                       |  |
|--------------------------------------|--|
| STANDARD INK CARTRIDGES              | 73N Black, 73N Cyan, 73N Magenta, 73N Yellow         |
| HIGH CAPACITY INK CARTRIDGE          | 73HN Black   |
| EXTRA HIGH CAPACITY INK CARTRIDGES   | 103 Black, 103 Cyan, 103 Magenta, 103 Yellow         |
| STANDARD INK CARTRIDGE YIELDS^^      | Approx. Black 245 pages, Colour Composite 340 pages  |
| HIGH CAPACITY INK CARTRIDGE YIELDS^^ | Approx. Black 410 pages                              |
| EXTRA HIGH CAPACITY                  |  |
| INK CARTRIDGE YIELDS^^               | Approx. Black 1035 pages. Colour Composite 865 pages |

- ^ Print speed (PPM) when printed on A4 plain paper in the fastest mode. 10x15cm photo print speed when printed on Epson Premium Glossy Photo Paper borderless in draft mode. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.
- $+ \ Copy \ speed \ when \ printed \ on \ plain \ paper \ in \ the \ fastest \ mode. \ Copy \ speed \ may \ vary \ depending \ on \ copy \ mode, \ document$ complexity, type of paper used and number of copies.
- ^^ According to ISO/IEC24711 and 24712 test suite. Click here for details on ISO testing. (PDF)

2.5" with tilt adjustment



LCD SCREEN















<sup>†</sup> Maximum pages per minute (PPM) are measured after first page with text patterns in Draft Mode on plain paper. ISO ppm is based on ISO/IEC 24734. Black and colour print speeds are determined in default, single-side mode, in accordance with ISO/IEC 24734. Actual print times will vary based on system configuration, software, and page complexity. See www.epson.com.au/printspeed for details, including complete ISO reports.

<sup>\*</sup>Some applications and/or functions, like two-sided printing, may not be supported by Mac®