



Smart concept; Smart design

Bright & Compact



Light Output **2500 lm**

Front Exhaust

USB Display

AV Mute
Slide Lens Shutter

W9/X9/S9 offers not just a stylish new design, but great performance as well. Its 2500 lumens allows for use in bright light conditions. Simple functions such as USB Display and Auto Source Search allow you to use the projector very easily.

- 5000 hour *E-TORL long-life lamp
- Quick Start-up 5 sec / Instant Off function
- Low standby power consumption (0,4W in Standby)
- 60 inch projection at 1.8m

*E-TORL Epson-Twin Optimize Reflection Lamp



Multimedia Projector EB-S9/EB-X9/EB-W9



AV Mute Slide Lens Shutter

Mute is achieved easily by closing the slide cover. This is convenient for situations like writing memos on the white board when using it as a screen, or even when you want to take a short break.



Front Exhaust

Positioning the projector exhaust in the front of the projector means no irritating hot air flow affecting the audience during desktop usage.

USB Display for Windows & Mac PC

Projection begins immediately by simply connecting the projector to a PC using the included USB cable. It's also possible to operate the mouse and page up/down between presentation pages with the remote controller.




SUPPLIED ACCESSORIES	
Power Cable 1.8m	
Remote Control	
With AA type alkaline batteries x 2pcs	
Computer Cable	
1.8m <6 ft>, AHD-15 pin type slim-cable	
Storage Case	
Password Protect Sticker	
Owner's Manual	
OPTIONAL ACCESSORIES	
ELPLP58	Spare Lamp
ELPAF25	Air Filter Set

SPECIFICATIONS			EB-S9	EB-X9	EB-W9
Specification of Main Parts	LCD	Size	0.55 inch (x 3)	0.55 inch (x 3)	0.59 inch (x 3)
		Pixel Number	480,000 dots (800 x 600) x 3	786,432 dots (1024 x 768) x 3	1,024,000 dots (1280 x 800) x 3
		Native Resolution	SVGA	XGA	WXGA
	Projection Lens		Manual focus & 1.35x digital zoom	Manual focus & 1.2x optical zoom	
		F=1.44 / F=16.6mm	F=1.58 - 1.72 / F=16.9 - 20.28mm		
Lamp	Type	200W UHE			
	Life	4000 hours (Power consumption: Normal) / 5000 hours (Power consumption: Eco)			
Screen Size		30 to 350 inch [0.87 to 10.5m]	30 to 300 inch [0.9 to 9.0m]	33 to 318 inch [0.9 to 9.0m]	
Offset		8:1		6:1	
Light Output*	Brightness Control Normal / Eco		2500 lm / 1960 lm		
Color Light Output*			2500 lm / 1960 lm		
Contrast*			2000:1		
Sound Output			1W monaural		
Analog RGB	Input Terminal	Video	D-sub 15-pin x 1		
		Audio	Stereo Mini x 1		
	Output Terminal	Video	D-sub 15-pin x 1		
		Audio	Stereo Mini x 1		
Video	Input Terminal	Video	Composite Video: RCA (Yellow) x 1		
			S-Video: Mini DIN x 1		
			Component Video: D-sub 15-pin x1 (in common with Analog RGB connector)		
		RGB Video: D-sub 15-pin x1 (in common with Analog RGB connector)			
	Audio	Stereo Mini x 1 (in common with Analog RGB Audio terminal)			
Control	Terminal	USB Type B x 1			
Operating Temperature			5°C to 35°C <41°F to 95°F>		
Operating Altitude			Up to 7,500 feet <2,286m> (over 4,921 feet <1,500m> area: with High Altitude mode)		
Start-Up Period			About 5 sec.		
Direct Power On			Yes		
Cool-Down Period			Instant off		
Power Supply Voltage			100 - 240V AC +/- 10%, 50/60Hz		
Power Consumption	100-120V	Lamp on	280W		
		Stand by	0.3W (Communication Off)		
	220-240V	Lamp on	265W		
		Stand by	0.4W (Communication Off)		
Dimensions Exclude Feet (D x W x H)				228 x 295 x 77	
Weight				Approx. 5.1 lbs. / 2.3 kg	
Fan Noise	Brightness Control : Normal / Eco			37dB / 29dB	

*Light Output / Color Light Output / Contrast — Color mode: Dynamic, Zoom: Wide

CONNECTOR PANEL



CONNECTOR PANEL	
1	Audio Out
2	Audio Input
3	S-Video Input
4	Video Input
5	USB (Type B)
6	Computer Input
7	Monitor Out

PROJECTION DISTANCE (EB-S9)

4:3 Screen size	Shortest (Wide)	Longest (Tele)	Offset (Wide)	Offset (Tele)
X (screen size / dimension)	Y (cm / inch)		Z (cm / inch)	Z (cm / inch)
60" / 120 cm x 91 cm 47.2" x 35.4"	177 / 70	240 / 95	10 / 3,9	3 / 1
80" / 160 cm x 120 cm 63.0" x 47.2"	237 / 93	321 / 126	13 / 5,2	3 / 1,3
100" / 200 cm x 150 cm 78.7" x 59.1"	297 / 117	402 / 158	17 / 6,5	4 / 1,7
200" / 410 cm x 300 cm 161.4" x 118.1"	597 / 235	807 / 318	33 / 13,1	9 / 3,4

PROJECTION DISTANCE (EB-X9)

4:3 Screen size	Shortest (Wide)	Longest (Tele)	Offset
X (screen size / dimension)	Y (cm / inch)		Z (cm / inch)
60" / 120cm x 91cm 47.2" x 35.4"	180 / 71	217 / 85	10 / 4
80" / 160 cm x 120 cm 63.0" x 47.2"	241 / 95	290 / 114	14 / 5,3
100" / 200 cm x 150 cm 78.8" x 59.1"	302 / 119	363 / 143	17 / 6,7
200" / 410 cm x 300 cm 161.4" x 118.1"	607 / 239	729 / 287	34 / 13,3

PROJECTION DISTANCE (EB-W9)

16:10 Screen size	Shortest (Wide)	Longest (Tele)	Offset
X (screen size / dimension)	Y (cm / inch)		Z (cm / inch)
60" / 130 cm x 81 cm 51.0" x 32.0"	168 / 66	202 / 79	12 / 4,5
80" / 170 cm x 110 cm 67.0" x 43.0"	225 / 88	270 / 106	15 / 6,1
100" / 220 cm x 130 cm 87.0" x 51.0"	281 / 111	338 / 133	19 / 7,6
200" / 430 cm x 270 cm 169.0" x 106.0"	566 / 223	680 / 268	38 / 15,1