PROJECTOR RANGE GUIDE

TRUE COLOURS
Brighter, vivid projection from Epson

3LCD

The best selling projectors #1 Epson Projectors in the world

EPSON

Note: Highlighted boxes indicate step-ups between models / within series	ENTRY BUSINESS				
	EB-W52*	**EB-FH52**	**EB-972**	**EB-982W**	**EB-992F**
Product Code	V11HA02053	V11H978053	V11H986053	V11H987053	V11H988053
IMAGE					
Light Source	Lamp	Lamp	Lamp	Lamp	Lamp
Resolution	WXGA	1080p	XGA	WXGA	1080p
Colour Light Output	4,000 lm	4,000 lm	4,100 lm	4,200 lm	4,000 lm
White Light Output	4,000 lm	4,000 lm	4,100 lm	4,200 lm	4,000 lm
Native Aspect Ratio	16:10	16:9	4:3	16:10	16:9
Contrast Ratio	16,000:1	16,000:1	16,000:1	16,000:1	16,000:1
Lamp Type	210 W UHE	230 W UHE	230 W UHE	230 W UHE	230 W UHE
Keystone Correction (Standard Lens)	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°
OPTICAL (for Standard Lens)					
Zoom	1 – 1.2 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	33" to 320"	30" to 300"	27" to 262"	29" to 280"	30" to 300"
Projection Distance	60" screen 1.68 m – 2.02 m	60" screen 1.76 m – 2.86 m	60" screen 1.93 m – 3.14 m	60" screen 1.79 m – 2.92 m	60" screen 1.76 m – 2.86 m
Throw Ratio	1.30 (Zoom: Wide) 1.56 (Zoom: Tele)	1.32 (Zoom: Wide) 2.14 (Zoom: Tele)	1.58 (Zoom: Wide) 2.56 (Zoom: Tele)	1.38 (Zoom: Wide) 2.24 (Zoom: Tele)	1.32 (Zoom: Wide) 2.14 (Zoom: Tele)
Focus Method	Manual	Manual	Manual	Manual	Manual
CONNECTIVITY					
Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)
Input: Computer	1 x D-sub 15-pin (RGB), 1 x USB 2.0 type B	1 x D-sub 15-pin (RGB), 1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B
Input: Digital	1 x HDMI	2 x HDMI	2 x HDMI	2 x HDMI	2 x HDMI
Input: Audio	1 x RCA (Red / White)	1 x RCA (Red / White)	1 x RCA (Red / White), 2 x Stereo mini	1 x RCA (Red / White), 2 x Stereo mini	1 x RCA (Red / White), 2 x Stereo mini
Control: I / O	-	-	1 x RS232C	1 x RS232C	1 x RS232C
Network: I / O	1 x USB 2.0 type A	1 x USB 2.0 type A	1 x RJ45, 1 x USB 2.0 type A (for Optional Wireless LAN)	1 x RJ45, 1 x USB 2.0 type A (for Optional Wireless LAN)	1 x RJ45, 1 x USB 2.0 type A
Wireless Connectivity	Included	Included	Optional (ELPAP11)	Optional (ELPAP11)	Included
Output: Video	-	-	1 x D-sub 15-pin	1 x D-sub 15-pin	1 x D-sub 15-pin
Output: Audio	-	-	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Built-in Speaker	2 W	16 W	16 W	16 W	16 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
Wireless LAN Enterprise Security	-	Yes	-	-	Yes
Miracast	-	Yes	-	-	Yes
Split Screen	Yes	Yes	Yes	Yes	Yes
Auto Keystone Correction	Vertical: ±30°	Vertical: ±30°	Vertical: ±30°	Vertical: ±30°	Vertical: ±30°
Horizontal Slide Keystone Correction	Yes	Yes	Yes	Yes	Yes
Instant Off	Yes	Yes	Yes	Yes	Yes
Direct Power On	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, password protect function				
Colour Modes	Dynamic, Presentation, Cinema, sRGB, Blackboard				
GENERAL					
Dimensions D x W x H (Including feet)	237 x 302 x 92 mm	293 x 309 x 105 mm	293 x 309 x 105 mm	293 x 309 x 105 mm	293 x 309 x 105 mm
Weight	2.6 kg	3.1 kg	3.1 kg	3.1 kg	3.1 kg
Lamp Life (Normal / Eco)	6,000 h / 12,000 h	5,500 h / 12,000 h	6,500 h / 17,000 h	6,500 h / 17,000 h	6,500 h / 17,000 h
Power Consumption: Lamp On	327 W	327 W	327 W	327 W	327 W
Power Consumption: Standby	2.0 W	2.0 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	37 / 28 dB	37 / 28 dB	37 / 28 dB	37 / 28 dB	37 / 28 dB

*NOT AVAILABLE IN NEW ZEALAND

Note: Highlighted boxes indicate step-ups between models / within series	PORTABLE BUSINESS		MID-RANGE BUSINESS		
	EB-1780W	**EB-1795F**	**EB-L260F**	**EB-2250U**	**EB-2265U**
Product Code	V11H795053	V11H796053	V11HA69053	V11H871053	V11H814053
IMAGE					
Light Source	Lamp	Lamp	Laser Diode	Lamp	Lamp
Resolution	WXGA	1080p	1080p	WUXGA	WUXGA
Colour Light Output	3,000 lm	3,200 lm	4,600 lm	5,000 lm	5,500 lm
White Light Output	3,000 lm	3,200 lm	4,600 lm	5,000 lm	5,500 lm
Native Aspect Ratio	16:10	16:9	16:9	16:10	16:10
Contrast Ratio	10,000:1	10,000:1	2,500,000:1	15,000:1	15,000:1
Lamp Type	206 W UHE	214 W UHE	Laser	300 W UHE	300 W UHE
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal: ±30°	Vertical: ±45° / Horizontal: ±30°	Vertical: ±30° / Horizontal: ±30°	Vertical: ±30° / Horizontal: ±30°	Vertical: ±30° / Horizontal: ±30°
OPTICAL (for Standard Lens)					
Zoom	1 – 1.2 (Optical)	1 – 1.2 (Optical)	1 – 1.62 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	30" to 300"	30" to 300"	31" to 310"	50" to 300"	50" to 300"
Projection Distance	60" screen 1.35 m – 1.62 m	60" screen 1.35 m – 1.64 m	62" screen 1.8 m	80" screen 2.36 m – 3.92 m	80" screen 2.36 m – 3.92 m
Throw Ratio	1.04 (Zoom: Wide) 1.26 (Zoom: Tele)	1.02 (Zoom: Wide) 1.23 (Zoom: Tele)	1.32 (Zoom: Wide) 2.12 (Zoom: Tele)	1.38 (Zoom: Wide) 2.28 (Zoom: Tele)	1.38 (Zoom: Wide) 2.28 (Zoom: Tele)
Focus Method	Manual	Powered	Manual	Manual	Manual
CONNECTIVITY					
Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)
Input: Computer	1 x D-sub 15-pin (RGB), 1 x USB 2.0 type B		2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B		
Input: Digital	1 x HDMI (1 x MHL)	1 x HDMI (1 x MHL)	2 x HDMI	2 x HDMI (1 x MHL)	2 x HDMI (1 x MHL), 1 x HDBaseT
Input: Audio	1 x Stereo mini	1 x Stereo mini	1 x RCA (Red / White), 2 x Stereo mini		
Control: I / O	1 x USB 2.0 type B	1 x USB 2.0 type B	1 x USB 2.0 type B, 1 x RS232C		
Network: I / O	1 x USB 2.0 type A	1 x USB 2.0 type A	1 x RJ45, 1 x USB 2.0 type A	1 x RJ45, 1 x USB 2.0 type A (for Optional Wireless LAN)	1 x RJ45, 1 x USB 2.0 type A
HDBaseT	-	-	-	-	Yes
Wireless Connectivity	Included	Included	Included	Optional (ELPAP10)	Included
Output: Video	-	-	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)
Output: Audio	-	-	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Built-in Speaker	1 W	1 W	16 W	16 W	16 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
Miracast	-	Yes	Yes	Yes	Yes
Split Screen	Yes	Yes	Yes	Yes	Yes
Auto Keystone Correction	Vertical: ±30°	Vertical: ±30°	Vertical: ±30° / Horizontal: ±30°	Vertical: ±30° / Horizontal: ±20°	Vertical: ±30° / Horizontal: ±20°
Gesture Presenter	-	Yes	-	Yes	Yes
NFC (Near Field Communication)	-	Yes	-	-	-
Screen Fit	-	Yes	-	Yes	Yes
Instant Off	Yes	Yes	Yes	Yes	Yes
Direct Power On	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, password protect function		Padlock & security cable hole, Kensington® – style lock provision, Wireless LAN unit lock, password protect function		
Colour Modes	Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM		Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM, Multi-Projection	Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM	
GENERAL					
Dimensions D x W x H (Including feet)	213 x 292 x 53 mm	213 x 292 x 53 mm	299 x 325 x 105 mm	291 x 377 x 110 mm	291 x 377 x 110 mm
Weight	1.8 kg	1.8 kg	4.2 kg	4.8 kg	4.9 kg
Light Source Life (Normal / Eco)	4,000 h / 7,000 h	4,000 h / 7,000 h	20,000 h / 30,000 h	5,000 h / 10,000 h	5,000 h / 10,000 h
Power Consumption: Lamp On	277 W	295 W	272 W	420 W	450 W
Power Consumption: Standby	2.0 W	2.0 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	39 / 30 dB	39 / 30 dB	36 / 27 dB	39 / 29 dB	39 / 29 dB

Note: Highlighted boxes indicate step-ups between models / within series	SHORT THROW	ULTRA SHORT THROW			
	EB-L210SF	**EB-685W**	**EB-770F**	**EB-805F**	**EB-810E**
Product Code	V11HA75053	V11H744553	V11HA79053	V11H923653	V11HA99053
IMAGE					
Light Source	Laser Diode	Lamp	Laser Diode	Laser Diode	Laser Diode
Resolution	1080p	WXGA	1080p	Full HD*	1080p
Colour Light Output	4,000 lm	3,500 lm	4,100 lm	5,000 lm	5,000 lm
White Light Output	4,000 lm	3,500 lm	4,100 lm	5,000 lm	5,000 lm
Native Aspect Ratio	16:9	16:10	16:9	16:9 up to 130"	16:9
Contrast Ratio	2,500,000:1	14,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Lamp Type	Laser	250 W UHE	Laser	Laser	Laser
Keystone Correction (Standard Lens)	Vertical: ±15° Horizontal: ±15°	Vertical: ±3° Horizontal: ±3°	Vertical: ±3° Horizontal: ±3°	Vertical:±3° Horizontal:±3°	-
OPTICAL (for Standard Lens)					
Zoom	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)
Screen Size	55" to 125"	60" to 100"	60" to 150" @ 16:9 57" to 142" @ 21:9	65" to 130" @ 16:9 61" to 120" @ 16:6	60" to 160" @ 16:9 57" to 150" @ 21:9
Projection Distance	90" screen 0.91 m	74.3" screen 0.44 m	77.0" screen 0.43 m	96" screen 0.80 m	90" screen 0.32 m
Throw Ratio	0.45 (Zoom: Wide) 0.61 (Zoom: Tele)	0.28 (Zoom: Wide) 0.37 (Zoom: Tele)	0.25 (Zoom: Wide) 0.35 (Zoom: Tele)	0.27 (Zoom: Wide) 0.37 (Zoom: Tele)	0.16 (Zoom: Wide) 0.22 (Zoom: Tele)
Focus Method	Manual	Manual	Manual	Manual	Manual
CONNECTIVITY					
Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	-
Input: Computer	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B				1 x USB 2.0 type B
Input: Digital	2 x HDMI	3 x HDMI (1 x MHL)	3 x HDMI	3 x HDMI	2 x HDMI
Input: Audio	1 x RCA (Red / White), 2 x Stereo mini, 1 x Mic-in Stereo mini	3 x Stereo mini, 1 x Mic-in Stereo mini		3 x Stereo mini	-
Control: I / O	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin	1 x RS-232C D-sub 9-pin
Network: I / O	1 x RJ45, 1 x USB type A (for Optional Wireless LAN)			1 x RJ45, 2 x USB type A (for Optional Wireless LAN)	
HDBaseT	-	-	-	Yes	Yes
Wireless Connectivity	Included	Optional (ELPAP10)	Included	Optional (ELPAP10)	Included
Output: Video	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB), 1 x HDMI	1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	-
ADVANCED FEATURES					
Built-in Speaker	16 W	16 W	16 W	16 W	16 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
4K Enhancement	-	-	-	-	Yes
Split Screen	Yes	Yes	Yes	Yes	Yes
Content Playback	Yes	Yes	Yes	Yes	Yes
High Dynamic Range	-	-	-	-	Yes
Scene Adaptive Gamma	Yes	-	Yes	-	Yes
Edgeblending	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, padlock & security cable hole, Wireless LAN unit lock, password protect function				
Colour Modes	Dynamic, Presentation, Cinema, sRGB, Blackboard, DICOM SIM, Multi-Projection				Dynamic, Presentation, Cinema, Natural, BlackBoard, DICOM SIM, Multi-Projection, Face brightness
GENERAL					
Dimensions D x W x H (Including Feet)	337 x 325 x 131 mm	400 x 367 x 187 mm	395 x 357 x 165 mm	450 x 458 x 227.5 mm	341 x 695 x 156 mm
Weight	4.6 kg	5.7 kg	5.9 kg	9.4 kg	12.5 kg
Light Source Life (Normal / Eco)	20,000 h / 30,000 h	5,000 h / 10,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h
Power Consumption: Lamp / LD On	260 W	354 W	263 W	366 W	380 W
Power Consumption: Standby	2.0 W	2.3 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	37 / 27 dB	35 / 30 dB	37 / 27 dB	36 / 27 dB	35 / 26 dB
Projector Wall Mount	Optional (ELPMB64)	Optional (ELPMB62)	Optional (ELPMB62)	Optional (ELPMB62)	Optional (ELPMB75)

*PIXEL SHIFTING TECHNOLOGY ACHIEVES FULL HD RESOLUTION ON SCREEN

Note: Highlighted boxes indicate step-ups between models / within series	INTERACTIVE ULTRA SHORT THROW			
	EB-760Wi	**EB-770Fi**	**EB-1480Fi**	**EB-1485Fi**
Product Code	V11HA80053	V11HA78053	V11H921553	V11H919053
IMAGE				
Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WXGA	1080p	Full HD*	Full HD*
Colour Light Output	4,100 lm	4,100 lm	5,000 lm	5,000 lm
White Light Output	4,100 lm	4,100 lm	5,000 lm	5,000 lm
Native Aspect Ratio	16:10	16:9	16:9 up to 100"	16:9 up to 100" 16:6 up to 120"
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Keystone Correction (Standard Lens)	Vertical: ±3° / Horizontal: ±3°	Vertical: ±3° / Horizontal: ±3°	Vertical: ±3° / Horizontal: ±3°	Vertical: ±3° / Horizontal: ±3°
OPTICAL (for Standard Lens)				
Zoom	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.35 (Digital)
Screen Size	58" to 146" @ 16:9 60" to 150" @ 16:10	60" to 150" @ 16:9 57" to 142" @ 21:9	65" to 100" @ 16:9	65" to 100" @ 16:9 61" to 120" @ 16:6
Projection Distance	74.3" screen 0.43 m	76" screen at 0.43 m	80" screen 0.49 m	80" screen 0.49 m
Throw Ratio	0.27 (Zoom: Wide) 0.37 (Zoom: Tele)	0.25 (Zoom: Wide) 0.35 (Zoom: Tele)	0.27 (Zoom: Wide) / 0.37 (Zoom: Tele)	
Focus Method	Manual	Manual	Manual	Manual
CONNECTIVITY				
Input: Video	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)	1 x RCA (Yellow)
Input: Computer	2 x RGB D-sub 15-pin, 2 x USB 2.0 type B			
Input: Digital	3 x HDMI	3 x HDMI	3 x HDMI	3 x HDMI, 1 x HDBaseT
Input: Audio	3 x Stereo mini, 1 x Mic-In Stereo mini			
Control: I / O	1 x RS-232C D-sub 9-pin, Interactive sync stereo mini - 1 x in / 1 x out, Touch Unit control - 1 x mini DIN 8-pin			
Network: I / O	1 x RJ45, 2 x USB type A (for Optional Wireless LAN)		1 x RJ45, 1 x USB type A (for Optional Wireless LAN)	
Touch Interactive	Mini DIN 8-pin	Mini DIN 8-pin	Mini DIN 8-pin	Mini DIN 8-pin
HDBaseT	-	-	-	Yes
Wireless Connectivity	Included	Included	Included	Included
Output: Video	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB), 1 x HDMI	1 x D-sub 15-pin (RGB), 1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES				
Built-in Speaker	16 W	16 W	2 x 8 W	2 x 8 W
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes
Interactivity	Pen Included, Finger Optional	Pen Included, Finger Optional	Pen Included, Finger Optional	Pen and Finger Included
Auto Screen Set Up	Yes	Yes	Yes	Yes
Miracast	Yes	Yes	Yes	Yes
Finger Touch Unit (FTU)	Optional (ELPFT01)			Included
Split Screen	Yes	Yes	Yes	Yes
Edge Blending	-	Yes	-	Yes
Scene Adaptive Gamma	Yes	Yes	-	-
Whiteboard Functioning	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes
FTU Mount	Optional (ELPMB63)			
Direct Power On / Off	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, padlock & security cable hole, Wireless LAN unit lock, password protect function			
GENERAL				
Dimensions D x W x H (Including Feet)	395 x 357 x 165 mm	395 x 357 x 165 mm	450 x 458 x 223.5 mm	450 x 458 x 223.5 mm
Weight	6 kg	6 kg	9.7 kg	9.7 kg
Light Source Life (Normal / Eco)	20,000 h / 30,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h	20,000 h / 30,000 h
Power Consumption: LD On	263 W	263 W	366 W	366 W
Power Consumption: Standby	2.0 W	2.0 W	2.0 W	2.0 W
Noise Level (Normal / Eco)	37 / 27 dB	37 / 27 dB	36 / 27 dB	36 / 27 dB
Projector Wall Mount	Optional (ELPMB62)			Included (ELPMB62)

*PIXEL SHIFTING TECHNOLOGY ACHIEVES FULL HD RESOLUTION ON SCREEN

Note: Highlighted boxes indicate step-ups between models / within series	LARGE VENUE						
	EB-L570U	**EB-L630U**	**EB-L730U**	**EB-L735U**	**EB-L630SU**	**EB-L635SU**	**EB-L770U**
Product Code	V11HA98053BU	V11HA26053BU	V11HA25053BU	V11HA25153BU	V11HA29053BU	V11HA29153BU	V11HA96053BU
IMAGE							
Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA
Colour Light Output	5,200 lm	6,200 lm	7,000 lm	7,000 lm	6,000 lm	6,000 lm	7,000 lm
White Light Output	5,200 lm	6,200 lm	7,000 lm	7,000 lm	6,000 lm	6,000 lm	7,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10	16:10	16:10	16:10
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
LD Input Power	185 W	219 W	236 W	236 W	211 W	211 W	233.6 W
Keystone Correction (Standard Lens)	Vertical: ±30° / Horizontal: ±30°						
Lens Shift (Standard Lens)	Vertical: ±50% / Horizontal: ±20%						
OPTICAL (for Standard Lens)							
Zoom	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.35 (Digital)	1 – 1.35 (Digital)	1 – 1.6 (Optical)
Screen Size	50" to 500"	50" to 500"	50" to 500"	50" to 500"	50" to 200"	50" to 200"	50" to 500"
Projection Distance	80" screen 2.33 m – 3.78 m				80" screen 1.38 m	80" screen 1.38 m	80" screen 2.33 m – 3.78 m
Throw Ratio	1.35 (Zoom: Wide) / 2.20 (Zoom: Tele)				0.80 (Zoom: Wide) / 1.07 (Zoom: Tele)		1.35 (Zoom: Wide) 2.20 (Zoom: Tele)
Focus Method	Manual	Manual	Manual	Manual	Manual	Manual	Manual
CONNECTIVITY							
Input: Computer	1 x USB 2.0 type B	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B					1 x USB 2.0 type B
Input: Digital	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT	2 x HDMI, 1 x HDBaseT
Input: Audio	-	2 x Stereo mini	2 x Stereo mini	2 x Stereo mini	2 x Stereo mini	2 x Stereo mini	-
Input Control: I / O	1 x RS-232C	1 x RS-232C	1 x RS-232C	1 x RS-232C	1 x RS-232C	1 x RS-232C	1 x RS-232C
Network I / O	2 x USB type A (1 x for optional Wireless LAN)*	1 x RJ45, 1 x USB type A (for optional Wireless LAN)*					2 x USB type A (1 x for optional Wireless LAN)*
HDBaseT	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Included	Included	Included	Included	Included	Optional (ELPAP11)
Output: Video	-	1 x D-sub 15-pin (RGB)					-
Output: Digital	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES							
Built-in Speaker	10 W	10 W	10 W	10 W	10 W	10 W	10 W
4K Enhancement	Yes	-	-	-	-	-	Yes
Epson Projector Management	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Epson iProjection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Epson Projector Content Manager	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN Unit)	Yes	Yes	Yes	Yes	Yes	Yes (with Optional Wireless LAN Unit)
Miracast	-	Yes	Yes	Yes	Yes	Yes	-
Split Screen	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	Yes	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Content Playback	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, Wireless LAN Unit Lock, Security cable hole						
GENERAL							
Dimensions D x W x H (Including Feet)	339 x 440 x 136 mm	339 x 440 x 136 mm	339 x 440 x 136 mm	339 x 440 x 136 mm	334 x 440 x 136 mm	334 x 440 x 136 mm	339 x 440 x 136 mm
Weight	8.3 kg	8.4 kg	8.4 kg	8.4 kg	8.4 kg	8.4 kg	8.5 kg
Power Consumption: LD On	312 W	345 W	345 W	345 W	345 W	345 W	366 W
Power Consumption: Standby	2 W	2 W	2 W	2 W	2 W	2 W	2 W
Noise Level (Normal/Eco)	31 / 23 dB	38 / 27 dB	38 / 27 dB	38 / 27 dB	38 / 27 dB	38 / 27 dB	38 / 27 dB

*WITH AN OPTIONAL ELPAP11, IT IS POSSIBLE TO USE THE MIRACAST AND WIFI FUNCTION SIMULTANEOUSLY (SIMPLE AP MODE AND MANUAL MODE)

Note: Highlighted boxes indicate step-ups between models / within series	LARGE VENUE*				
	EB-PU1007WNL	**EB-PU1008WNL**	**EB-PU1008BNL**	**EB-PU2010WNL**	**EB-PU2010BNL**
Product Code	V11HA34953BU	V11HA33953BU	V11HA33853BU	V11HA52953BU	V11HA52853BU
IMAGE					
Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA
Colour Light Output	7,000 lm	8,500 lm	8,500 lm	10,000 lm	10,000 lm
White Light Output	7,000 lm	8,500 lm	8,500 lm	10,000 lm	10,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10	16:10
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
LD Input Power	291 W	372 W	372 W	388 W	388 W
Referenced Standard Lens	ELPLM08	ELPLM08	ELPLM08	ELPLM15	ELPLM15
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal: ±30°				
Lens Shift (Standard Lens)	Vertical: ±67% / Horizontal: ±30%			Vertical: ±60% / Horizontal: ±18%	
OPTICAL (for Standard Lens)					
Zoom	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)
Screen Size	50" to 1000"	50" to 1000"	50" to 1000"	60" to 1000"	60" to 1000"
Projection Distance	100" screen 3.11 m – 5 m			100" screen 3.38 m – 5.52 m	
Throw Ratio	1.44 (Zoom: Wide) / 2.32 (Zoom: Tele)			1.57 (Zoom: Wide) / 2.56 (Zoom: Tele)	
Focus Method	Powered	Powered	Powered	Powered	Powered
CONNECTIVITY					
Input: Computer	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)
Input: Digital	1 x HDMI, 1 x DVI-D, 1 x HDBaseT			1 x HDMI, 1 x DVI-D, 1 x HDBaseT	
Input: SDI	-	-	-	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Control: I / O	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini
Network: I / O	1 x RJ45, 1 x USB type A (for Optional Wireless LAN)				
HDBaseT	Yes	Yes	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)
Output: Digital	-	-	-	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes	Yes
Epson iProjection (Multi-PC Projection)	Yes	Yes	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes	Yes	Yes
Remote Access Camera	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)
External Air Filter (High capacity)	Optional (ELPAF63)	Optional (ELPAF63)	Optional (ELPAF63)	Optional (ELPAF63)	Optional (ELPAF63)
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN Unit)				
4K Enhancement	Yes	Yes	Yes	Yes	Yes
Art-Net	Yes	Yes	Yes	Yes	Yes
Lens Position Memory	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)
Split Screen	Yes	Yes	Yes	Yes	Yes
Edge Blending	Yes	Yes	Yes	Yes	Yes
Curved Screen Projection	Yes	Yes	Yes	Yes	Yes
Frame Interpolation	Yes	Yes	Yes	Yes	Yes
Super-resolution	Yes	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes	Yes
Security	Kensington® – style lock provision, Wireless LAN Unit Lock, Security cable hole				
Colour Modes	Dynamic, Presentation, Cinema, BT.709, Natural, DICOM SIM, Multi-Projection				
GENERAL					
Dimensions D x W x H (Including Feet)	436 x 545 x 189 mm	436 x 545 x 189 mm	436 x 545 x 189 mm	436 x 545 x 189 mm	436 x 545 x 189 mm
Weight	16.4 kg	16.4 kg	16.4 kg	17.0 kg	17.0 kg
Power Consumption: LD On	366 W	452 W	452 W	452 W	452 W
Noise Level (Normal/Eco)	34 / 30 dB	36 / 30 dB	36 / 30 dB	37 / 30 dB	37 / 30 dB

Note: Highlighted boxes indicate step-ups between models / within series	LARGE VENUE*			
	EB-PU2213B	**EB-PU2216B**	**EB-PU2220B**	**EB-L30000UNL**
Product Code	V11HA68853BU	V11HA67853BU	V11HA66853BU	V11H944853BU
IMAGE				
Light Source	Laser Diode	Laser Diode	Laser Diode	Laser Diode
Resolution	WUXGA	WUXGA	WUXGA	WUXGA
Colour Light Output	13,000 lm	16,000 lm	20,000 lm	30,000 lm
White Light Output	13,000 lm	16,000 lm	20,000 lm	30,000 lm
Native Aspect Ratio	16:10	16:10	16:10	16:10
Contrast Ratio	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
LD Input Power	562 W	746 W	934 W	1,670 W
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal ±30°	Vertical: ±45° / Horizontal ±30°	Vertical: ±44° / Horizontal ±30°	Vertical: ±45°/ Horizontal ±30°
Lens Shift (Standard Lens)	Vertical: ±60% / Horizontal: ±18%	Vertical: ±60% / Horizontal: ±18%	Vertical: ±60% / Horizontal: ±18%	Vertical: ±65% / Horizontal: ±30%
OPTICAL (for Standard Lens)				
Zoom	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.6 (Optical)	1 – 1.35 (Optical)
Screen Size	60" to 1000"	60" to 1000"	60" to 1000"	100" to 1000"
Projection Distance	100" screen 3.37 m – 5.49 m	100" screen 3.37 m	100" screen 3.37 m	200" screen 7.48 m – 10.11 m
Throw Ratio	1.57 (Zoom: Wide) / 2.56 (Zoom: Tele)			1.74 (Zoom: Wide) 2.35 (Zoom: Tele)
Focus Method	Powered	Powered	Powered	Powered
CONNECTIVITY				
Input: Video	-	-	-	1 x 5BNC
Input: Computer	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)	1 x D-sub 15-pin (RGB)
Input: Digital	1 x HDMI, 1 x DVI-D, 1 x HDBaseT			1 x HDMI, 1 x DVI-D, 1 x HDBaseT
Input: SDI	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Control: I / O	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini	1 x RS232C, 1 x Stereo mini
Network: I / O	1x RJ45 (Art-Net), 1 x USB type A (for Optional Wireless LAN), 1 x USB type B (service)			
HDBaseT	Yes	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)
Output: Digital	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)	1 x BNC (3G-SDI)
Output: Audio	1 x Stereo mini	1 x Stereo mini	1 x Stereo mini	-
ADVANCED FEATURES				
Epson Projector Management (Network & Control)	Yes	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes	Yes
Remote Access Camera	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN Unit)	Yes (with Optional Wireless LAN Unit)	Yes (with Optional Wireless LAN Unit)	Yes (with Optional Wireless LAN Unit)
4K Enhancement	Yes	Yes	Yes	Yes
Fully Sealed Optical Engine	Yes	Yes	Yes	Yes
Art-Net	Yes	Yes	Yes	Yes
Lens Position Memory	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)	Yes (10 positions)
Split Screen	Yes	Yes	Yes	Yes
Edge Blending	Yes	Yes	Yes	Yes
Scaling	Yes	Yes	Yes	Yes
Curved Screen Projection	Yes	Yes	Yes	Yes
Simple Stacking	Yes	Yes	Yes	Yes
NFC	Yes	Yes	Yes	-
Gamma Correction	Yes	Yes	Yes	Yes
Frame Interpolation	Yes	Yes	Yes	Yes
Super-resolution	Yes	Yes	Yes	Yes
Detail Enhancement	Yes	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes	Yes
Instant Off	Yes	Yes	Yes	Yes

* PLEASE VISIT WWW.EPSON.COM.AU FOR DIMENSIONS AND WEIGHT OF ABOVE MODELS

Note: Highlighted boxes indicate step-ups between models / within series	LARGE VENUE*		
	EB-PQ2010B	**EB-PQ2216B**	**EB-PQ2220B**
Product Code	V11HB02853BU	V11HB04853BU	V11HB05853BU
IMAGE			
Light Source	Laser Diode	Laser Diode	Laser Diode
Resolution	4K** (3840 x 2160, 8.3 million pixels)	4K** (3840 x 2160, 8.3 million pixels)	4K** (3840 x 2160, 8.3 million pixels)
Colour Light Output	10,000 lm	16,000 lm	20,000 lm
White Light Output	10,000 lm	16,000 lm	20,000 lm
Native Aspect Ratio	16:9		
Contrast Ratio	5,000,000:1		
LD Input Power	449 W	810 W	1080 W
Keystone Correction (Standard Lens)	Vertical: ±45° / Horizontal ±30°		
Lens Shift (Standard Lens)	Vertical: ±58% / Horizontal: ±16%		
OPTICAL (for Standard Lens)			
Zoom	1 – 1.61 (Optical)		
Screen Size	60" to 1000"		
Projection Distance	100" screen 3.35 m		
Throw Ratio	1.52 (Zoom: Wide) / 2.47 (Zoom: Tele)		
Focus Method	Powered		
CONNECTIVITY			
Input: Digital	2 x HDMI, 1 x HDBaseT, 1 x BNC (12G-SDI)		
Input: SDI	1 x BNC (12G-SDI)		
Control: I / O	1 x RS232C, 1 x Stereo mini		
Network: I / O	1x RJ45 (Art-Net), 1 x USB type A (for Optional Wireless LAN)		
HDBaseT	Yes	Yes	Yes
Wireless Connectivity	Optional (ELPAP11)	Optional (ELPAP11)	Optional (ELPAP11)
Output: Digital	1 x HDMI, 1 x BNC (12G-SDI)		
Output: Audio	1 x Stereo mini		
ADVANCED FEATURES			
Epson Projector Management (Network & Control)	Yes	Yes	Yes
Epson Professional Tool	Yes	Yes	Yes
Epson Projector Content Manager	Yes	Yes	Yes
Wireless LAN Enterprise Security	Yes (with Optional Wireless LAN unit)		
Remote Access Camera	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)	Yes (with Optional ELPEC01)
Fully Sealed Optical Engine	-	Yes	Yes
Art-Net	Yes	Yes	Yes
Fully Sealed Laser Light Source	-	Yes	Yes
Edge Blending	Yes	Yes	Yes
Scaling	Yes	Yes	Yes
Curved Surface Blending Support	Yes	Yes	Yes
NFC	Yes	Yes	Yes
Simple Stacking	Yes	Yes	Yes
Simple Blending	Yes	Yes	Yes
Scene Adaptive Gamma	Yes	Yes	Yes
Frame Interpolation (4K @ 120 Hz)	Yes	Yes	Yes
Super-resolution	Yes	Yes	Yes
360 Degrees Projection	Yes	Yes	Yes
HDR10 (High Dynamic Range)	Yes	Yes	Yes
HLG (Hybrid Log Gamma)	Yes	Yes	Yes
Auto Contrast Enhancement	Yes	Yes	Yes
Auto Signal Backup Function	Yes (HDMI, SDI, HDBaseT)		
Colour Modes	Dynamic, Presentation, Cinema, BT.709, Natural, DICOM SIM, Multi-Projection		

* PLEASE VISIT WWW.EPSON.COM.AU FOR DIMENSIONS AND WEIGHT OF ABOVE MODELS

** 1080P WITH 2-AXIS PIXEL SHIFT TECHNOLOGY. ON SCREEN PIXELS = 8,294,400 DOTS (1,920 X 1,080 X 4).

Note: Highlighted boxes indicate step-ups between models / within series	LIGHTING		HOME THEATRE		
	EV-110	**EV-115**	**CO-FH02**	**EH-TW6250**	**EH-TW7100**
Product Code	V11HA22053	V11HA22153	V11HA85053	V11HA73053	V11H959053
IMAGE					
Light Source	Laser Diode	Laser Diode	Lamp	Lamp	Lamp
Resolution	WXGA	WXGA	1080p	4K Enhancement* (1920 x 1080 x 2)	4K Enhancement* (1920 x 1080 x 2)
Colour Light Output	2,200 lm	2,200 lm	3,000 lm	2,800 lm	3,000 lm
White Light Output	2,200 lm	2,200 lm	3,000 lm	2,800 lm	3,000 lm
Native Aspect Ratio	16:10	16:10	16:9	16:9	16:9
Contrast Ratio	2,500,000:1	2,500,000:1	350:1	35,000:1	100,000:1
Lamp Type	Laser	Laser	188 W UHE	200 W UHE	250 W UHE
Keystone Correction (Standard Lens)	Vertical: ±45° Horizontal: ±40°	Vertical: ±45° Horizontal: ±40°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°	Vertical: ±30° Horizontal: ±30°
Lens Shift	-	-	-	Vertical: ±60%	Vertical: ±60% Horizontal: ±24%
Colour Processing	10-bit	10-bit	8-bit	10-bit	10-bit
OPTICAL (for Standard Lens)					
Zoom	Total: 1 – 2.2 (Optical: 1 – 1.58, Digital: 1 – 1.4)		1 – 1.35 (Digital)	1 – 1.62 (Optical)	1 – 1.6 (Optical)
Screen Size	30" to 150"	30" to 150"	26" to 391"	40" to 500"	40" to 500"
Projection Distance	60" screen 1.79 m	60" screen 1.79 m	60" screen 1.58 m	80" screen 2.34 m – 3.81 m	100" screen 2.95 m – 4.77 m
Throw Ratio	1.38 (Zoom: Wide) / 2.19 (Zoom: Tele)		1.19 (Zoom: Wide) 1.61 (Zoom: Tele)	1.32 (Zoom: Wide), 2.15 (Zoom: Tele)	1.32 (Zoom: Wide) 2.15 (Zoom: Tele)
Focus Method	Powered	Powered	Manual	Manual	Manual
CONNECTIVITY					
Input: Digital	1 x HDMI	1 x HDMI	1 x HDMI	1 x HDMI	2 x HDMI
Input: SD Card	1 x SDHC, up to 32 GB		-	-	-
USB: I / O	1 x USB type A zoom A (Power Supply)	1 x USB type A zoom A (Power Supply)	1 x USB type A (Power Supply, Firmware Update, copy OSD settings), 1 x USB B mini (service)	1 x USB mini B (service)	1 x USB type A (Power Supply, Firmware Update), 1 x USB B mini (service)
Control	1 x USB type A for GPI	1 x USB type A for GPI	-	-	1 x RS232C, 1 x Stereo mini
Network: I / O	1 x RJ45	1 x RJ45	-	-	1 x USB type A (for Optional Wireless LAN)
Wireless Connectivity	Included	Included	Included (via SMP)	Included (via SMP)	Optional (ELPAP10)
Output: Audio	1 x Stereo mini	1 x Stereo mini	-	1 x Stereo mini	1 x Stereo mini
ADVANCED FEATURES					
Built-in Speaker	-	-	5 W	10 W	2 x 10 W
Epson Projector Management (Network & Control)	Yes	Yes	-	-	-
Scene Adaptive Gamma	-	-	Yes	Yes	-
High Dynamic Range	-	-	-	Yes	Yes
Detail Enhancement	-	-	-	Yes	Yes
4K Enhancement	-	-	-	Yes	Yes
Smart Media Player Included	-	-	Yes	Yes	-
Edge Blending	Yes	Yes	-	-	-
Frame Interpolation	-	-	-	Yes	Yes
360 Degrees Projection	Yes	Yes	-	-	-
Content Playback Features	Playlists, Timetables (Scheduled Playlists), SD Viewer Movies (Motion, JPEG), Photos		-	-	-
Security	Password protect function		Kensington® – style lock provision, password protect function		
Colour Modes	Dynamic, Normal		Dynamic, Vivid, Natural, Cinema		Dynamic, Bright Cinema, Natural, Cinema
GENERAL					
Dimensions D x W x H (Including Feet)	Projection unit: 175 x D265 Power supply unit: 110 x 459 x 65 mm (with Cable Cover)		211 x 320 x 87 mm	275 x 333 x 131 mm	330 x 410 x 164 mm
Weight	6.9 kg	6.9 kg	2.6 kg	4.1 kg	6.9 kg
Lamp Life (Normal / Eco)	-	-	6,000 h / 12,000 h	4,500 h / 7,500 h	3,500 h / 5,000 h
Power Consumption: Light Source On	170 W	170 W	270 W	301 W	406 W
Power Consumption: Standby	2.0 W	2.0 W	-	-	2.0 W

*4K ENHANCEMENT TECHNOLOGY (4KE) SHIFTS EACH PIXEL DIAGONALLY TO DOUBLE FULL HD (1920 X 1080) RESOLUTION.

Note: Highlighted boxes indicate step-ups between models / within series	HOME THEATRE		ULTRA SHORT THROW HOME	
	EH-TW9400	**EH-LS12000B**	**EH-LS650B**	**EH-LS800B**
Product Code	V11H928053	V11HA47053	V11HB07153	V11HA90153
IMAGE				
Light Source	Lamp	Laser diode	Laser diode	Laser diode
Resolution	4K Enhancement* (1920 x 1080 x 2)	4K* (1920 x 1080 x 4)	4K Enhancement* (1920 x 1080 x 2)	4K Enhancement* (1920 x 1080 x 2)
Colour Light Output	2,600 lm	2,700 lm	3,600 lm	4,000 lm
White Light Output	2,600 lm	2,700 lm	3,600 lm	4,000 lm
Native Aspect Ratio	16:9	16:9	16:9	16:9
Contrast Ratio	1,200,000:1	2,500,000:1	Over 2,500,000:1	2,500,000:1
Lamp Type	250 W UHE	Laser	Laser	Laser
Keystone Correction (Standard Lens)	Vertical: ±30°	Vertical: ±30° Horizontal: ±30°	-	-
Lens Shift (Standard Lens)	Vertical: ±96.3% / Horizontal: ±47.1%	Vertical: ±96.3% / Horizontal: ±47.1%	-	-
Colour Processing	10-bit	10-bit	10-bit	10-bit
Advanced Image Processing	Yes	Yes (32-bit)	Yes	Yes
OPTICAL (for Standard Lens)				
Zoom	1 – 2.1 (Optical)	1 – 2.1 (Optical)	1 – 2.5 (Digital)	1 – 2.5 (Digital)
Screen Size	50" to 300"	50" to 300"	60" to 120"	32" to 150"
Projection Distance	100" screen 3 m – 6.3 m	100" screen 3 m – 6.3 m	77" screen 0.43 m	90" screen 0.32 m
Throw Ratio	1.35 (Zoom: Wide) 2.84 (Zoom: Tele)	1.35 (Zoom: Wide) 2.84 (Zoom: Tele)	0.25 (Zoom: Wide) 0.62 (Zoom: Tele)	0.16 (Zoom: Wide) 0.40 (Zoom: Tele)
Focus Method	Powered	Powered	Manual	Manual
CONNECTIVITY				
Input: Computer	1 x D-sub 15-pin (RGB)	-	-	-
Input: Digital	2 x HDMI	2 x HDMI (HDCP2.3) (HDMI2 supports eARC/ARC)	2 x HDMI (HDCP2.3) (HDMI2 supports eARC)	3 x HDMI (HDCP2.3) (HDMI2 supports ARC)
USB: I / O	2 x USB type A 1 x USB B mini (service)	2 x USB type A (1x Opt. HDMI) 1 x USB B mini (service)	3x USB type A (2x for data, 1x for 5V/2A power supply), 1x USB B mini (service only)	1 x USB type A, 1 x USB B mini (service)
Control: I / O	1 x RS232C	1 x RS232C	-	-
Network: I / O	1 x RJ45, 1 x USB type A (for Optional Wireless LAN)	1 x RJ45	-	3 x USB type A (for 5V / 2A Power Supply Only)
Wireless Connectivity	Optional (ELPAP10)	-	Included	Included
Output: Audio	1 x Stereo mini	1 x Stereo mini	1x S / PDIF	1 x S / PDIF 1 x Stereo mini
ADVANCED FEATURES				
Built-in Speaker	-	-	20 W (2 x 2.1ch Satellite, 1 x Subwoofer)	20 W (2 x 2.1ch Satellite, 1 x Subwoofer)
Super Resolution	Yes	Yes (4K compatible)	Yes	Yes
High Dynamic Range - HDR10	Yes	Yes (HDR10+)	Yes	Yes
Hybrid Log Gamma - HLG	Yes	Yes	Yes	Yes
4K Enhancement*	Yes	Yes	Yes	Yes
Frame Interpolation	Yes	Yes (up to 4K 60fps)	Yes	Yes
Smart Media Player	-	Optional (ELPAP12)	Yes	Yes
Auto Contrast Enhancement	-	Yes	Yes	Yes
Scene Adaptive Gamma	-	Yes	Yes	Yes
Direct Power On	Yes	Yes	-	-
Security	Kensington® – style lock provision	Kensington® – style lock provision	Kensington® – style lock provision	Kensington® – style lock provision
Colour Modes	2D: Dynamic, Bright Cinema, Natural Cinema, Digital Cinema 3D: 3D Dynamic, 3D Cinema	Dynamic, Bright Cinema, Cinema, Natural, Vivid	Dynamic, Vivid, Cinema, Natural	Dynamic, Vivid, Cinema, Natural
GENERAL				
Dimensions D x W x H (Including Feet)	450 x 520 x 192.7 mm	447 x 520 x 192.7 mm	400 x 467 x 153 mm	341 x 695 x 156 mm
Weight	11.2 kg	12.7 kg	7.4 kg	12.3 kg
Light Source Life (Normal / Eco)	3,500 h / 5,000 h	20,000 h / 30,000 h	20,000 h	20,000 h

*4K RESOLUTION ENHANCEMENT TECHNOLOGY SHIFTS EACH PIXEL TO PRODUCE AN IMAGE ON SCREEN, UP TO THE STATED SPECIFICATION.

OPTIONAL LENSES

EB-L30000U

Lens type	Rear Projection	Wide Zoom	Wide Zoom	Mid Throw	Mid Throw	Mid Throw	Long Throw	Long Throw
Reference	ELPLR05	ELPLU05	ELPLW07	ELPLM12	ELPLM13	ELPLM14	ELPLL09	ELPLL10
Order Number	V12H004X0A	V12H004X0B	VI2H004W07	VI2H004M0D	VI2H004M0E	VI2H004L09	VI2H004R05	VI2H004R05
Throw Ratio	0.63	0.90 – 1.09	1.29 – 1.76	1.74 – 2.35	2.28 – 3.46	3.41 – 5.11	4.79 – 7.20	6.73 – 10.45

EB-PU Series

Lens type	Ultra Short-Throw	Ultra Short-Throw	Short Throw	Short Throw	Wide Throw	Wide Throw	Wide Throw	Mid Throw	Mid Throw	Mid Throw	Mid Throw	Long Throw
Reference	ELPLX01S	ELPLX02S	ELPLU03S	ELPLU04	ELPLW05	ELPLW06	ELPLW08	ELPLM08	ELPLM15	ELPLM10	ELPLM11	ELPLL08
Order Number	VI2H004X01	VI2H004X02	VI2H004UA3	VI2H004U04	VI2H004W05	VI2H004W06	VI2H004W08	VI2H004M08	VI2H004M08	VI2H004M0A	VI2H004M0B	VI2H004L08
Throw Ratio	0.35:1	-	0.65 – 0.78:1	0.87 – 1.06:1	1.04 – 1.46:1	1.63 – 2.22:1	1.18 – 1.66:1	1.45 – 2.32:1	2.15 – 3.49:1	3.31 – 5.07:1	4.48 – 7.39:1	7.2 – 10.12:1
PU2213B / PU2216B / PU2220B	-	0.35:1	0.48 – 0.57:1	0.64 – 0.78:1	0.77 – 1.07:1	1.19 – 1.63:1	0.86 – 1.21:1	1.08 – 1.72:1	1.58 – 2.56:1	2.43 – 3.71:1	3.54 – 5.41:1	5.27 – 7.41:1

OPTIONS AND ACCESSORIES

Air Filters

Regularly replace the air filter in your Epson projector in order to maintain image quality and to ensure longevity.

Lamps

Order genuine Epson lamps to ensure that you achieve the best possible image quality and colour reproduction.

Speakers

Enhance the audio experience with the Epson ELP-SP02 powered speaker set.

Control Pad

A simple cable management solution from Epson. Ideal for classrooms and meeting spaces.

Streaming Media Player

Stream your favourite content with the ELPAP12.

Portable Screen

Epson portable, light weight 120 inch screen is the perfect display solution for your home or office.

Ceiling Mounts

Ceiling mounts to suit all models of Epson projectors.

Wireless LAN Adapter

A simple yet powerful solution to enabling wireless connectivity to your Epson projector (optional models only).

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

Epson Australia Pty Ltd
Level 1, 3 Talavera Road
Macquarie Park NSW 2113
Tel: 02 8899 3666
www.epson.com.au

ABN: 91 002 625 783

Epson New Zealand
Level 2, 9 Fanshawe Street
Auckland 1010
Tel: 09 366 6855
www.epson.co.nz

August 2024

EPSON